

AA26003787

Architectural Building Requirements for Bulow Shores Homeowners Association
Client Name:
Address:
Lot #:
Home Style:
Date:
NOTE: DOES and or SHOULD MEET CRITERIA
1.) Minimum Building Size:
1,800 square feet minimum (heated or air conditioned) exclusive of porches, garages, decks and other unheated spaces.
2.) Building Heights:
Maximum height of dwellings can be 3 stories not to exceed 40 feet.
3.) Finished Floor Elevations: (Confirmed by Civil)
Each lot has a specific assigned minimum floor elevation.
4.) Exterior Materials:
Siding of cementation composure, composite, stucco, or wood are acceptable but must be easy to maintain.
Finish material consistent on all sides of the building.
Metal and vinyl siding, exposed concrete block, imitation asphalt brick siding, and tarpaper are prohibited.
All materials proposed for exterior use may be assessed by the ARB prior to construction. The ARB may require sample materials for review.
5.) Exterior Features:
Exterior windows and door trim and similar shall be of the same, complementing, or contrasting color and material. Compatibility should be considered by the ARB in accepting proposed trim and decoration.

I	Page 2 – Lot #
	Any architectural appointments or trim details must be consistent with architectural style of the structure.
	All windows must be single, double hung, or casement and the style shall be consistent with the architectural style of the home.
	Screens are permitted but must have gray screening material.
	Aluminum awnings, reflective glass, and jalousie-type windows are prohibited.
	Highest quality windows and fixed glass that are impact resistant are required.
	The use of glass block windows shall be limited to the side and rear of the structure.
	Exterior doors and sidelights with stained, colored, leaded, or etched glass may be permitted with ARB approval.
	Doors constructed of wood or fiberglass and encased in wood surrounds are encouraged on the front of the house. Glass in doors and sliding/folding glass doors must be impact resistant.
	Reflective glass shall be prohibited.
	Screening of front porches and entrance is prohibited.
	Screening on side and rear porches and patios, if desired, must look as if the porch or patio is open with architectural features intact.
	To promote indoor, outdoor transitions, the creative use of wide verandas on the rear of the homes is strongly encouraged.
(5.) Exterior Colors
	The color palette shall be subdued earth colors/tones and pastels and shall be compatible with architectural style of the home.
	All paints shall resist chalking and fading for a 10 year life cycle.
•	7.) Roofs
	The preferred and encouraged composition of all roofs shall be tile, slate, metal, and shingles with colors and specifications that must be submitted to the ARB.

Flat roofs are prohibited on the main portion of the structure, however, the ARB shall have

6:12. Other pitches may be considered on a case by case basis by ARB.

discretion to approve such roofs if consistent with the architectural style.

Roof pitches must be compatible with the architectural style of the home, but must not be less than

Flues and vents shall be on the rear slope of the building as not to be visible from the street and must blend in with the color of the roofing material. Skylights may be approved for the front of the slope on a case by case basis by ARB.
Solar energy producing devices (active or passive) must be approved by the ARB and must be removed from the view of adjacent streets and properties when feasible.
8.) Chimneys
Any exposed portions of a chimney outside of the building shall be constructed solely of brick, stone or stucco.
Metal fireplace types (self-insulated) with metal spark arrester at the top of the chimney, must have a cowling or surround of a material approved in advance in writing by the ARB and be color approved. No unpainted aluminum or other metal may be exposed.
Chimneys, porch towers, or catwalks constructed as an integral part of the main dwelling may extend up to 50 feet in height.
9.) Garages
No garage shall be less than 400 square feet of total floor space for automobiles, not including space required for hot water heaters, HVAC equipment, and other equipment and appliances commonly located in garages.
All garages must be constructed of the same exterior materials and colors as the main dwelling.
Rigid panel garage doors are prohibited.
No carports shall be permitted.
10.) Energy Efficiency
All homes must meet or exceed Florida's Energy Efficiency Code for building construction.
11.) Antennas
Antennas, aerials and similar equipment including satellite dishes and antennas are encouraged to be placed, screened, or landscaped so as to be hidden from view as long as such landscaping or placement does not affect the quality of the reception or unreasonably increase the cost of obtaining the antenna.
12.) Window Air Conditioners
No window air conditioners shall be permitted.
13). Hurricane shutters
Hurricane shutters, supports, and hardware are subject to the review and approval of the ARB.
Any supports or hardware that remain permanent elements, shall be finished to match the adjacent architectural element.



AA26003787

Page 4 – Lot # _____

Architectural Building Requirements for Patten Company Seaside Landir	1gs
Client Name:	
Address:	
.ot # <u>:</u>	
Home Style:	
Date:	



AA26003787

Architectural Building Requirements for Bulow Shores Homeowners Association
Client Name:
Address:
Lot #:
Home Style:
Date:
NOTE: DOES and or SHOULD MEET CRITERIA
1.) Minimum Building Size:
1,800 square feet minimum (heated or air conditioned) exclusive of porches, garages, decks and other unheated spaces.
2.) Building Heights:
Maximum height of dwellings can be 3 stories not to exceed 40 feet.
3.) Finished Floor Elevations: (Confirmed by Civil)
Each lot has a specific assigned minimum floor elevation.
4.) Exterior Materials:
Siding of cementation composure, composite, stucco, or wood are acceptable but must be easy to maintain.
Finish material consistent on all sides of the building.
Metal and vinyl siding, exposed concrete block, imitation asphalt brick siding, and tarpaper are prohibited.
All materials proposed for exterior use may be assessed by the ARB prior to construction. The ARB may require sample materials for review.
5.) Exterior Features:
Exterior windows and door trim and similar shall be of the same, complementing, or contrasting color and material. Compatibility should be considered by the ARB in accepting proposed trim and decoration.

I	Page 2 – Lot #
	Any architectural appointments or trim details must be consistent with architectural style of the structure.
	All windows must be single, double hung, or casement and the style shall be consistent with the architectural style of the home.
	Screens are permitted but must have gray screening material.
	Aluminum awnings, reflective glass, and jalousie-type windows are prohibited.
	Highest quality windows and fixed glass that are impact resistant are required.
	The use of glass block windows shall be limited to the side and rear of the structure.
	Exterior doors and sidelights with stained, colored, leaded, or etched glass may be permitted with ARB approval.
	Doors constructed of wood or fiberglass and encased in wood surrounds are encouraged on the front of the house. Glass in doors and sliding/folding glass doors must be impact resistant.
	Reflective glass shall be prohibited.
	Screening of front porches and entrance is prohibited.
	Screening on side and rear porches and patios, if desired, must look as if the porch or patio is open with architectural features intact.
	To promote indoor, outdoor transitions, the creative use of wide verandas on the rear of the homes is strongly encouraged.
(5.) Exterior Colors
	The color palette shall be subdued earth colors/tones and pastels and shall be compatible with architectural style of the home.
	All paints shall resist chalking and fading for a 10 year life cycle.
•	7.) Roofs
	The preferred and encouraged composition of all roofs shall be tile, slate, metal, and shingles with colors and specifications that must be submitted to the ARB.

Flat roofs are prohibited on the main portion of the structure, however, the ARB shall have

6:12. Other pitches may be considered on a case by case basis by ARB.

discretion to approve such roofs if consistent with the architectural style.

Roof pitches must be compatible with the architectural style of the home, but must not be less than

Flues and vents shall be on the rear slope of the building as not to be visible from the street and must blend in with the color of the roofing material. Skylights may be approved for the front of the slope on a case by case basis by ARB.
Solar energy producing devices (active or passive) must be approved by the ARB and must be removed from the view of adjacent streets and properties when feasible.
8.) Chimneys
Any exposed portions of a chimney outside of the building shall be constructed solely of brick, stone or stucco.
Metal fireplace types (self-insulated) with metal spark arrester at the top of the chimney, must have a cowling or surround of a material approved in advance in writing by the ARB and be color approved. No unpainted aluminum or other metal may be exposed.
Chimneys, porch towers, or catwalks constructed as an integral part of the main dwelling may extend up to 50 feet in height.
9.) Garages
No garage shall be less than 400 square feet of total floor space for automobiles, not including space required for hot water heaters, HVAC equipment, and other equipment and appliances commonly located in garages.
All garages must be constructed of the same exterior materials and colors as the main dwelling.
Rigid panel garage doors are prohibited.
No carports shall be permitted.
10.) Energy Efficiency
All homes must meet or exceed Florida's Energy Efficiency Code for building construction.
11.) Antennas
Antennas, aerials and similar equipment including satellite dishes and antennas are encouraged to be placed, screened, or landscaped so as to be hidden from view as long as such landscaping or placement does not affect the quality of the reception or unreasonably increase the cost of obtaining the antenna.
12.) Window Air Conditioners
No window air conditioners shall be permitted.
13). Hurricane shutters
Hurricane shutters, supports, and hardware are subject to the review and approval of the ARB.
Any supports or hardware that remain permanent elements, shall be finished to match the adjacent architectural element.



AA26003787

Page 4 – Lot # _____

Architectural Building Requirements for Patten Company Seaside Landir	1gs
Client Name:	
Address:	
.ot # <u>:</u>	
Home Style:	
Date:	



AA26003787

Architectural Building Requirements for Bulow Shores Homeowners Association
Client Name:
Address:
Lot #:
Home Style:
Date:
NOTE: DOES and or SHOULD MEET CRITERIA
1.) Minimum Building Size:
1,800 square feet minimum (heated or air conditioned) exclusive of porches, garages, decks and other unheated spaces.
2.) Building Heights:
Maximum height of dwellings can be 3 stories not to exceed 40 feet.
3.) Finished Floor Elevations: (Confirmed by Civil)
Each lot has a specific assigned minimum floor elevation.
4.) Exterior Materials:
Siding of cementation composure, composite, stucco, or wood are acceptable but must be easy to maintain.
Finish material consistent on all sides of the building.
Metal and vinyl siding, exposed concrete block, imitation asphalt brick siding, and tarpaper are prohibited.
All materials proposed for exterior use may be assessed by the ARB prior to construction. The ARB may require sample materials for review.
5.) Exterior Features:
Exterior windows and door trim and similar shall be of the same, complementing, or contrasting color and material. Compatibility should be considered by the ARB in accepting proposed trim and decoration.

I	Page 2 – Lot #
	Any architectural appointments or trim details must be consistent with architectural style of the structure.
	All windows must be single, double hung, or casement and the style shall be consistent with the architectural style of the home.
	Screens are permitted but must have gray screening material.
	Aluminum awnings, reflective glass, and jalousie-type windows are prohibited.
	Highest quality windows and fixed glass that are impact resistant are required.
	The use of glass block windows shall be limited to the side and rear of the structure.
	Exterior doors and sidelights with stained, colored, leaded, or etched glass may be permitted with ARB approval.
	Doors constructed of wood or fiberglass and encased in wood surrounds are encouraged on the front of the house. Glass in doors and sliding/folding glass doors must be impact resistant.
	Reflective glass shall be prohibited.
	Screening of front porches and entrance is prohibited.
	Screening on side and rear porches and patios, if desired, must look as if the porch or patio is open with architectural features intact.
	To promote indoor, outdoor transitions, the creative use of wide verandas on the rear of the homes is strongly encouraged.
(5.) Exterior Colors
	The color palette shall be subdued earth colors/tones and pastels and shall be compatible with architectural style of the home.
	All paints shall resist chalking and fading for a 10 year life cycle.
•	7.) Roofs
	The preferred and encouraged composition of all roofs shall be tile, slate, metal, and shingles with colors and specifications that must be submitted to the ARB.

Flat roofs are prohibited on the main portion of the structure, however, the ARB shall have

6:12. Other pitches may be considered on a case by case basis by ARB.

discretion to approve such roofs if consistent with the architectural style.

Roof pitches must be compatible with the architectural style of the home, but must not be less than

Flues and vents shall be on the rear slope of the building as not to be visible from the street and must blend in with the color of the roofing material. Skylights may be approved for the front of the slope on a case by case basis by ARB.
Solar energy producing devices (active or passive) must be approved by the ARB and must be removed from the view of adjacent streets and properties when feasible.
8.) Chimneys
Any exposed portions of a chimney outside of the building shall be constructed solely of brick, stone or stucco.
Metal fireplace types (self-insulated) with metal spark arrester at the top of the chimney, must have a cowling or surround of a material approved in advance in writing by the ARB and be color approved. No unpainted aluminum or other metal may be exposed.
Chimneys, porch towers, or catwalks constructed as an integral part of the main dwelling may extend up to 50 feet in height.
9.) Garages
No garage shall be less than 400 square feet of total floor space for automobiles, not including space required for hot water heaters, HVAC equipment, and other equipment and appliances commonly located in garages.
All garages must be constructed of the same exterior materials and colors as the main dwelling.
Rigid panel garage doors are prohibited.
No carports shall be permitted.
10.) Energy Efficiency
All homes must meet or exceed Florida's Energy Efficiency Code for building construction.
11.) Antennas
Antennas, aerials and similar equipment including satellite dishes and antennas are encouraged to be placed, screened, or landscaped so as to be hidden from view as long as such landscaping or placement does not affect the quality of the reception or unreasonably increase the cost of obtaining the antenna.
12.) Window Air Conditioners
No window air conditioners shall be permitted.
13). Hurricane shutters
Hurricane shutters, supports, and hardware are subject to the review and approval of the ARB.
Any supports or hardware that remain permanent elements, shall be finished to match the adjacent architectural element.



AA26003787

Page 4 – Lot # _____

Architectural Building Requirements for Patten Company Seaside Landir	1gs
Client Name:	
Address:	
.ot # <u>:</u>	
Home Style:	
Date:	



AA26003787

Architectural Building Requirements for Bulow Shores Homeowners Association
Client Name:
Address:
Lot #:
Home Style:
Date:
NOTE: DOES and or SHOULD MEET CRITERIA
1.) Minimum Building Size:
1,800 square feet minimum (heated or air conditioned) exclusive of porches, garages, decks and other unheated spaces.
2.) Building Heights:
Maximum height of dwellings can be 3 stories not to exceed 40 feet.
3.) Finished Floor Elevations: (Confirmed by Civil)
Each lot has a specific assigned minimum floor elevation.
4.) Exterior Materials:
Siding of cementation composure, composite, stucco, or wood are acceptable but must be easy to maintain.
Finish material consistent on all sides of the building.
Metal and vinyl siding, exposed concrete block, imitation asphalt brick siding, and tarpaper are prohibited.
All materials proposed for exterior use may be assessed by the ARB prior to construction. The ARB may require sample materials for review.
5.) Exterior Features:
Exterior windows and door trim and similar shall be of the same, complementing, or contrasting color and material. Compatibility should be considered by the ARB in accepting proposed trim and decoration.

ſ	Page 2 – Lot #
	Any architectural appointments or trim details must be consistent with architectural style of the structure.
	All windows must be single, double hung, or casement and the style shall be consistent with the architectural style of the home.
	Screens are permitted but must have gray screening material.
	Aluminum awnings, reflective glass, and jalousie-type windows are prohibited.
	Highest quality windows and fixed glass that are impact resistant are required.
	The use of glass block windows shall be limited to the side and rear of the structure.
	Exterior doors and sidelights with stained, colored, leaded, or etched glass may be permitted with ARB approval.
	Doors constructed of wood or fiberglass and encased in wood surrounds are encouraged on the front of the house. Glass in doors and sliding/folding glass doors must be impact resistant.
	Reflective glass shall be prohibited.
	Screening of front porches and entrance is prohibited.
	Screening on side and rear porches and patios, if desired, must look as if the porch or patio is open with architectural features intact.
	To promote indoor, outdoor transitions, the creative use of wide verandas on the rear of the homes is strongly encouraged.
(5.) Exterior Colors
	The color palette shall be subdued earth colors/tones and pastels and shall be compatible with architectural style of the home.
	All paints shall resist chalking and fading for a 10 year life cycle.
7	7.) Roofs
	The preferred and encouraged composition of all roofs shall be tile, slate, metal, and shingles with colors and specifications that must be submitted to the ARB.

Flat roofs are prohibited on the main portion of the structure, however, the ARB shall have

6:12. Other pitches may be considered on a case by case basis by ARB.

discretion to approve such roofs if consistent with the architectural style.

Roof pitches must be compatible with the architectural style of the home, but must not be less than

Flues and vents shall be on the rear slope of the building as not to be visible from the street and must blend in with the color of the roofing material. Skylights may be approved for the front of the slope on a case by case basis by ARB.
Solar energy producing devices (active or passive) must be approved by the ARB and must be removed from the view of adjacent streets and properties when feasible.
8.) Chimneys
Any exposed portions of a chimney outside of the building shall be constructed solely of brick, stone or stucco.
Metal fireplace types (self-insulated) with metal spark arrester at the top of the chimney, must have a cowling or surround of a material approved in advance in writing by the ARB and be color approved. No unpainted aluminum or other metal may be exposed.
Chimneys, porch towers, or catwalks constructed as an integral part of the main dwelling may extend up to 50 feet in height.
9.) Garages
No garage shall be less than 400 square feet of total floor space for automobiles, not including space required for hot water heaters, HVAC equipment, and other equipment and appliances commonly located in garages.
All garages must be constructed of the same exterior materials and colors as the main dwelling.
Rigid panel garage doors are prohibited.
No carports shall be permitted.
10.) Energy Efficiency
All homes must meet or exceed Florida's Energy Efficiency Code for building construction.
11.) Antennas
Antennas, aerials and similar equipment including satellite dishes and antennas are encouraged to be placed, screened, or landscaped so as to be hidden from view as long as such landscaping or placement does not affect the quality of the reception or unreasonably increase the cost of obtaining the antenna.
12.) Window Air Conditioners
No window air conditioners shall be permitted.
13). Hurricane shutters
Hurricane shutters, supports, and hardware are subject to the review and approval of the ARB.
Any supports or hardware that remain permanent elements, shall be finished to match the adjacent architectural element.



AA26003787

Page 4 – Lot # _____

Architectural Building Requirements for Patten Company Seaside Landir	1gs
Client Name:	
Address:	
.ot # <u>;</u>	
Home Style:	
Date:	



AA26003787

Architectural Building Requirements for Bulow Shores Homeowners Association
Client Name:
Address:
Lot #:
Home Style:
Date:
NOTE: DOES and or SHOULD MEET CRITERIA
1.) Minimum Building Size:
1,800 square feet minimum (heated or air conditioned) exclusive of porches, garages, decks and other unheated spaces.
2.) Building Heights:
Maximum height of dwellings can be 3 stories not to exceed 40 feet.
3.) Finished Floor Elevations: (Confirmed by Civil)
Each lot has a specific assigned minimum floor elevation.
4.) Exterior Materials:
Siding of cementation composure, composite, stucco, or wood are acceptable but must be easy to maintain.
Finish material consistent on all sides of the building.
Metal and vinyl siding, exposed concrete block, imitation asphalt brick siding, and tarpaper are prohibited.
All materials proposed for exterior use may be assessed by the ARB prior to construction. The ARB may require sample materials for review.
5.) Exterior Features:
Exterior windows and door trim and similar shall be of the same, complementing, or contrasting color and material. Compatibility should be considered by the ARB in accepting proposed trim and decoration.

ſ	Page 2 – Lot #
	Any architectural appointments or trim details must be consistent with architectural style of the structure.
	All windows must be single, double hung, or casement and the style shall be consistent with the architectural style of the home.
	Screens are permitted but must have gray screening material.
	Aluminum awnings, reflective glass, and jalousie-type windows are prohibited.
	Highest quality windows and fixed glass that are impact resistant are required.
	The use of glass block windows shall be limited to the side and rear of the structure.
	Exterior doors and sidelights with stained, colored, leaded, or etched glass may be permitted with ARB approval.
	Doors constructed of wood or fiberglass and encased in wood surrounds are encouraged on the front of the house. Glass in doors and sliding/folding glass doors must be impact resistant.
	Reflective glass shall be prohibited.
	Screening of front porches and entrance is prohibited.
	Screening on side and rear porches and patios, if desired, must look as if the porch or patio is open with architectural features intact.
	To promote indoor, outdoor transitions, the creative use of wide verandas on the rear of the homes is strongly encouraged.
(5.) Exterior Colors
	The color palette shall be subdued earth colors/tones and pastels and shall be compatible with architectural style of the home.
	All paints shall resist chalking and fading for a 10 year life cycle.
7	7.) Roofs
	The preferred and encouraged composition of all roofs shall be tile, slate, metal, and shingles with colors and specifications that must be submitted to the ARB.

Flat roofs are prohibited on the main portion of the structure, however, the ARB shall have

6:12. Other pitches may be considered on a case by case basis by ARB.

discretion to approve such roofs if consistent with the architectural style.

Roof pitches must be compatible with the architectural style of the home, but must not be less than

Flues and vents shall be on the rear slope of the building as not to be visible from the street and must blend in with the color of the roofing material. Skylights may be approved for the front of the slope on a case by case basis by ARB.
Solar energy producing devices (active or passive) must be approved by the ARB and must be removed from the view of adjacent streets and properties when feasible.
8.) Chimneys
Any exposed portions of a chimney outside of the building shall be constructed solely of brick, stone or stucco.
Metal fireplace types (self-insulated) with metal spark arrester at the top of the chimney, must have a cowling or surround of a material approved in advance in writing by the ARB and be color approved. No unpainted aluminum or other metal may be exposed.
Chimneys, porch towers, or catwalks constructed as an integral part of the main dwelling may extend up to 50 feet in height.
9.) Garages
No garage shall be less than 400 square feet of total floor space for automobiles, not including space required for hot water heaters, HVAC equipment, and other equipment and appliances commonly located in garages.
All garages must be constructed of the same exterior materials and colors as the main dwelling.
Rigid panel garage doors are prohibited.
No carports shall be permitted.
10.) Energy Efficiency
All homes must meet or exceed Florida's Energy Efficiency Code for building construction.
11.) Antennas
Antennas, aerials and similar equipment including satellite dishes and antennas are encouraged to be placed, screened, or landscaped so as to be hidden from view as long as such landscaping or placement does not affect the quality of the reception or unreasonably increase the cost of obtaining the antenna.
12.) Window Air Conditioners
No window air conditioners shall be permitted.
13). Hurricane shutters
Hurricane shutters, supports, and hardware are subject to the review and approval of the ARB.
Any supports or hardware that remain permanent elements, shall be finished to match the adjacent architectural element.



AA26003787

Page 4 – Lot # _____

Architectural Building Requirements for Patten Company Seaside Landir	1gs
Client Name:	
Address:	
.ot # <u>;</u>	
Home Style:	
Date:	